2007

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 136

City of Waynesboro

Information in this report is included in Report

07

(Augusta County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

Special Routes

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Wavnesboro

									Tru	ıck			K		Dir		
Route	Jurisdiction	1	Length	AADT	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW
East 64	From:			CL Waynest													
64	City of Waynesboro (` ,	0.23	18000	F	87%	1%	1%	1%	10%	0%	F -	NA			17000	G
	Combined Traffic Estimates for 2 Parallel	Roadways on this	Route:		F	87%	1%	1%	1%	10%	0%	F	NA			35000	G
East	To: From:			US 340													
64)	City of Waynesboro ((Maint: 07)	1.95	18000	Α	87%	1%	1%	1%	10%	0%	С	0.103	Α		18000	Α
	Combined Traffic Estimates for 2 Parallel	Roadways on this	Route:	37000	Α	87%	1%	1%	1%	10%	0%	С	0.106	Α	0.570	36000	Α
East	To: From:		Delphi	ne Ave, To	07-624												
East 64	City of Waynesboro ((Maint: 07)	0.70	16000	F	87%	1%	1%	1%	10%	0%	F	NA			16000	G
••	Combined Traffic Estimates for 2 Parallel	` '			F	87%	1%	1%	1%	10%	0%	F	NA			31000	G
	To:			L Waynesb	oro												
Vest	From:		WC	L Waynest	oro												
64)	City of Waynesboro ((Maint: 07)	0.43	18000	F	88%	1%	1%	1%	9%	0%	F	NA			17000	G
\smile	Combined Traffic Estimates for 2 Parallel	Roadways on this	Route:	36000	F	87%	1%	1%	1%	10%	0%	F	NA			35000	G
West	Ta: From:			US 340													
64	City of Waynesboro ((Maint: 07)	2.15	19000	Α	88%	1%	1%	1%	9%	0%	С	0.118	Α		18000	Α
04)	Combined Traffic Estimates for 2 Parallel	` '			Α	87%	1%	1%	1%	10%	0%	С	0.106	Α	0.570	36000	Α
	To:			ne Ave, To													
Vest	From: L	(Mainte 07)	•	-		000/	40/	40/	40/	00/	00/	_	NIA			45000	_
64	Combined Tarffic Fatire to 6 to 2 Recelled	` ,	0.30	16000	F	88%	1%	1%	1%	9%	0%	F F	NA			15000	G
	Combined Traffic Estimates for 2 Parallel	Roadways on this		32000 L Waynesb	F oro	87%	1%	1%	1%	10%	0%	г	NA			31000	G
	From:			L Waynest													
250 Main St	City of Waynes	boro	0.84	21000	F	99%	0%	0%	0%	0%	0%	F	0.088	F	0.502	23000	F
250)	To:			Carman Ave													
250 Main St	From: L City of Waynes	boro	0.30	20000	F	99%	0%	0%	0%	0%	0%	F	0.086	F	0.517	21000	F
250)	To:					0070	0,0		0,70	0,0	0,0	•	0.000	•	0.0	2.000	
250 Main St	From: L City of Waynes	horo	0.67	opeman Pkv 13000	F	99%	0%	0%	0%	0%	0%	F	0.095	F	0.513	14000	F
250) Wall of	To:					0070	070		070	070	070	•	0.000	•	0.010	14000	•
250 Broad St	From: City of Waynes	horo	0.25	340 Rosser 12000	Ave F	99%	0%	0%	0%	0%	0%	F	0.084	F	0.536	13000	F
250 Bload St	City of Waynes					3370	070	078	0 70	070	078	'	0.004	'	0.550	13000	'
250 Broad St	City of Wayness	horo	0.50	Poplar Ave 12000	F	99%	0%	0%	0%	0%	0%	F	0.084	F	0.561	13000	F
250 Bload St	City of Waynes	50010				9976	076	0 /6	076	0 /0	0 /6		0.004		0.501	13000	
Droad Ct	To: From:	horo		Wayne Ave		000/	00/		00/	00/	00/		0.002		0.561	11000	
Broad St	City of Waynes	DOIO	0.12	10000	F	99%	0%	0%	0%	0%	0%	F	0.083	F	0.561	11000	F
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	To: From:		0.44	Arch Ave		200/	00/		00/	40/	00/		0.00:	_	0.50	11000	
250 Broad St	City of Waynes	boro	0.44	10000	F	98%	0%	1%	0%	1%	0%	С	0.081	F	0.53	11000	F
-	From:			S 340 Main S 340 Broad													
250 340 Main St	City of Waynes	boro	0.19	12000	F	98%	0%	1%	0%	1%	0%	F	0.092	F	0.53	13000	F
200 040	To:			40 Delphine													

### Virginia Department of Transportation Traffic Engineering Division

### 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Waynesboro

_				_			Tru	ck			K		Dir		
Route	Jurisdiction	Length AADT (	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	Q۷
~~	From:	Delphine Ave													
250 Main St	City of Waynesboro	1.00 <b>7100</b>	F	96%	0%	1%	0%	2%	0%	F	0.092	F	0.593	7700	F
~	To- From:	Hunter St													
Main St	City of Waynesboro	0.44 <b>7000</b>	F	96%	0%	1%	0%	2%	0%	С	0.093	F	0.602	7600	F
~ <i>_</i>	To:	ECL Waynesboro	)												
_	From:	WCL Waynesboro													
₂₅₄ ) Ivy St	City of Waynesboro	1.19 <b>5200</b>	F	97%	0%	1%	1%	1%	0%	С	0.100	F	0.584	5700	
<u> </u>	To: From:	Hopeman Pkwy				<b>—</b>									
lvy St	City of Waynesboro	0.52 <b>5600</b>	F	97%	0%	1%	1%	1%	0%	F	0.095	F	0.640	6100	
$\mathcal{L}$	To	King Ave													
Poplar Ave	City of Waynesboro		F	98%	1%	1%	0%	0%	0%	С	0.089	F	0.539	11000	-
	To	D 1 C4													
Poplar Ave	City of Waynesboro	Broad St 0.07 <b>3300</b>	F	98%	1%	1%	0%	0%	0%	F	0.113	F	0.594	3600	
254)1 opiai Ave	To:	Main St	•	3070	170		070	070	070		0.113	•	0.004	3000	
	From:	WCL Waynesboro	^												
Rosser Ave	City of Waynesboro			96%	1%	1%	1%	2%	0%	F	0.081	F	0.586	19000	
340 1100001 7110	and a may have a second		•	0070	170		170	_,0	070	•	0.001	•	0.000	10000	
Pagas Ava	City of Waynesboro	I-64 0.56 <b>26000</b>	F	97%	0%	1%	0%	1%	0%	С	0.086	F	0.525	28000	
Rosser Ave	City of Waynesboro			91%	0%	1%	0%	170	0%	C	0.066	Г	0.525	28000	
~~	To: From:	Lew Dewitt Blvd													
Rosser Ave	City of Waynesboro	0.71 <b>16000</b>	F	99%	0%	1%	0%	0%	0%	С	0.086	F	0.515	17000	
	To: From:	Northgate Ave													
Rosser Ave	City of Waynesboro	0.61 <b>13000</b>	F	99%	0%	1%	0%	0%	0%	F	0.086	F	0.504	14000	
<del>~</del>	Too	Forrest Dr				<u> </u>									
Rosser Ave	City of Waynesboro	0.56 <b>13000</b>	F	99%	0%	1%	0%	0%	0%	F	0.086	F	0.510	14000	- 1
<del></del>	To:	US 250 Main St													
~~~	From	Rosser Ave	_	000/	00/		00/	007	00/	_	0.004	_	0.547	0000	
Main St	City of Waynesboro	0.38 7500	F	99%	0%	1%	0%	0%	0%	F	0.091	F	0.517	8200	
~~	To: From:	New Hope Rd													
Main St	City of Waynesboro	0.35 6800	F	99%	0%	1%	0%	0%	0%	F	0.094	F	0.547	7300	
~	To- From:	Wayne Ave													
Main St	City of Waynesboro	0.14 3500	F	99%	0%	1%	0%	0%	0%	F	0.094	F	0.545	3700	
<i>~</i>	To:	Arch Ave				<u> </u>									
Main St	City of Waynesboro		F	99%	0%	1%	0%	0%	0%	F	0.091	F	0.572	6300	
	Tol	US 250 Broad St													
340)(250) Main St	City of Waynesboro		F	98%	0%	1%	0%	1%	0%	F	0.092	F	0.53	13000	
340)(250) Wall St	Oity of VV ayricsbold		•	5070	070	1 /0	070	1 /0	070	'	0.002	'	0.00	13000	
~~~	To: From	Main St	_	0501	461		461	00.1	001		0.65.		0.500	10000	_
Delphine Ave	City of Waynesboro		F	95%	1%	1%	1%	2%	0%	F	0.091	F	0.593	12000	F
<u>~</u>	To:	7th St													

5/14/2008 8

## Virginia Department of Transportation Traffic Engineering Division 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Wavnesboro

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
340 Delphine Ave	City of Waynesboro	0.60	7th St	F	95%	1%	1%	1%	2%	0%	F	0.089	F	0.578	12000	F
340 Bolphine 7 Ve	To Food		Second St	•	3070	170	/°	170	270			0.000		0.070	12000	
0340 Delphine Ave	City of Waynesboro	0.81	9000	F	95%	1%	1%	1%	2%	0%	F	0.092	F	0.599	9800	F
	To: From:	He	opeman Pkv	vy												
(340) Delphine Ave	City of Waynesboro	0.25	9300	F	95%	1%	1%	1%	2%	0%	С	0.093	F	0.632	10000	F
<u> </u>	То:	NC	L Waynesb	oro												

# Virginia Department of Transportation Traffic Engineering Division 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Waynesboro

						,	vv ayrı <del>c</del> sb									
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
City of Waynesboro		From:	1			116 34	Dossar Ax									
F ₂₀₉ Shenandoah Village Dr	0.27	NA				US 34	O Rosser Av	e			NA			NA		
3		To				D	ead End									
_		From				US 34	O Rosser Av	e								
(F210)	0.04	NA									NA			NA		
<u> </u>		To:				D	ead End									
	0.40	From:				SCL	Waynesboro	1						NIA		0.4/4.7/000
F211)	0.40	580 To:	R			07 1040 E	CL Waynes	horo			NA			NA		04/17/20
		From:						10010								
1 Kirby St	0.12	310	F	94%	3%	2%	andoah Ave 0%	0%	0%	С	0.109	F	0.593	340	F	2007
1)	02	To:		0.70	0,0		A Street	070	0,70			•	0.000	0.0		200.
		From:				K	irby Ave									
2 A St	0.22	1300	F	98%	1%	1%	0%	0%	0%	С	0.111	F	0.635	1400	F	2007
<u>-)</u>		To				ECL '	Waynesboro	)								
_		From				Ro	sser Ave									
Thirteenth St	0.63	4200	F	98%	0%	1%	0%	0%	0%	F	0.102	F	0.597	4500	F	2007
$\overline{}$		To:				P	ine Ave				$\neg$ —					
Thirteenth St	0.43	2600	F	98%	0%	1%	0%	0%	0%	С	0.098	F	0.544	2800	F	2007
		To				A	rch Ave									
_		From:				Nor	thgate Ave									
Davis Rd	0.09	930	F	99%	0%	1%	0%	0%	0%	F	0.105	F	0.527	1000	F	2007
<u> </u>		To: From:					edette St									
Vedette Ave	0.68	860	F	99%	0%	1%	oavis Rd 0%	0%	0%	С	0.098	F	0.520	940	F	2007
Sion Voucillo / 110	0.00	To:		0070	070		Main St	070	070				0.020	0.10	·	2001
		From:				D	avis Rd									
Northgate Ave	0.33	2200	F	99%	0%	1%	0%	0%	0%	С	0.094	F	0.59	2400	F	2007
$\bigcup$		To					owbrook Ro	l								
Mandaukunal Dd	0.70	From:	ᄂ	000/	00/		thgate Ave	00/	00/		0.400	_	0.500	2200	_	2007
Meadowbrook Rd	0.76	3000 To:	F	99%	0%	0%	0% dhurst Rd	0%	0%	С	0.103	F	0.568	3200	F	2007
		From:														
5104) Hopeman Pkwy	0.89	9700	F	96%	1%	1%	Main St 1%	2%	0%	F	0.091	F	0.524	10000	F	2007
Hopeman Pkwy	0.00	T			170				070		- O.OO .		0.021	10000	·	2001
5104) Hopeman Pkwy	0.96	8800	F	96%	1%	1%	Ivy St 1%	2%	0%	F	0.099	F	0.539	9600	F	2007
5104) Hopeman Fkwy	0.90	0000		90 /6	1 /0			2 /0	0 76		0.099		0.559	9000	-	2007
O Hanaman Divisi	0.50	From	ᄂ	000/	40/		ing Ave	20/	00/	_			0.570	7700		2007
5104) Hopeman Pkwy	0.58	7100		96%	1%	1%	1%	2%	0%	F	0.102	F	0.578	7700	F	2007
		From:	<u> </u>				nicom Dr									
5104 Hopeman Pkwy	0.29	6500 To:	F	96%	1%	1%	1%	2%	0%	С	0.098	F	0.603	7000	F	2007
			1				phine Ave									
5105) Lyndhurst Rd	1.61	2900	F	99%	0%	SWCL 1%	Waynesboi		0%	С	0.098	F	0.570	2200	F	2007
5105) Lynanurst Ra	1.01	2900		99%	076		0%	0%	0%	C	0.096	Г	0.579	3200	г	2007
Luna alla uma ti Dal	0.05	From:	ᄂ	000/	00/		owbrook Ro		00/		0404	_	0.574	<i></i>		2007
5105 Lyndhurst Rd	0.65	5100	F	99%	0%	1%	0%	0%	0%	F	0.101	F	0.571	5500	F	2007
		From:	<u> </u>				odrow Ave					_				
Wayne Ave	0.37	5500	F	99%	0%	1%	0%	0%	0%	F	0.105	F	0.562	6000	F	2007
		From:					13th St				$\Box$					
(5105) Wayne Ave	0.47	4400	F	99%	0%	1%	0%	0%	0%	F	0.104	F	0.507	4800	F	2007
<u> </u>		To: From:					50 Broad St Ohio St				-					
5105) Florence Ave	0.83	1600	F	99%	0%	1%	0%	0%	0%	F	0.096	F	0.618	1700	F	2007
5,103)		To:			2,0		idge Ave		2,0			_				
		From:					ead End									
(5106) New Hope Rd	0.59	560	F	99%	0%	1%		0%	0%	F	0.128	F	0.531	600	F	2007
(5)(06) 11011 11010 110					0,0	1 /0	0%	U /0	U /0		0.120		0.551	000		

# Virginia Department of Transportation Traffic Engineering Division 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Waynesboro

Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
City of Waynesboro		From				~ "	2 17				- 1					
5106) Whitebridge Rd	0.98	900	F	99%	0%	Guil 1%	ford Lane 0%	0%	0%	С	0.110	F	0.527	970	F	2007
5106) Whitebridge Rd	0.90	<b>300</b>		99 /0	0 /0		Waynesboro		0 /6		0.110		0.521	910		2007
		From	<u> </u>					,			+					
5107) King Ave	0.62	3300	F	98%	0%	1%	Ivy St 0%	0%	0%	F	0.097	F	0.589	3600	F	2007
King Ave	0.02	3300		30 70	0 70	1 70	0 70	0 70	070	'	0.037	•	0.505	3000	•	2001
	0.57	From	<u> </u>	000/	00/		ridge St	201	001			_	0.500	0000		000
5107 King Ave	0.57	3100 To	F	98%	0%	1%	0%	0%	0%	С	0.115	F	0.508	3300	F	2007
		10	1				man Pkwy									
$\bigcirc$ 5	0.00	From	<u> </u>	000/	00/		3th St	201	00/			_	0.540	0000	_	000-
Poplar Ave	0.29	2400 _{To}	F	98%	0%	1%	0%	0%	0%	F	0.122	F	0.543	2600	F	2007
							Iain St									
O 14/1 - D.1	0.40	From	<u> </u>	000/	00/		ohine Ave	201	00/			_	0.500	0000	_	000
5109 Windsor Rd	0.43	3500	F	99%	0%	1%	0%	0%	0%	С	0.107	F	0.582	3800	F	2007
							dhurst Rd									
O 0.		From	<u> </u>				rlotte Ave				<b>_</b>	_			_	
5110) 4th St	0.31	420	F	99%	0%	1%	0%	0%	0%	F	0.111	F	0.535	460	F	2007
<u> </u>		To From				Delj	ohine Ave				$\Box$					
5110) 4th St	0.46	2100	F	99%	0%	1%	0%	0%	0%	С	0.09	F	0.558	2300	F	2007
$\overline{}$		To				Jack	kson Ave									
<u> </u>		From				Wa	yne Ave									
Arch Ave	0.85	2900	F	97%	1%	1%	1%	1%	0%	С	0.089	F	0.5	3100	F	2007
<u> </u>		To				В	road St									
		From				Норе	man Pkwy									
5112) Bridge Ave	1.02	1700	F	99%	0%	1%	0%	0%	0%	С	0.098	F	0.54	1900	F	2007
		To				ī	Bath St									
Second St	0.24	4400 From	F	99%	0%	1%	0%	0%	0%	F	0.086	F	0.591	4800	F	2007
5112	•	To					ohine Ave			-		-				
		From	1				Iain St									
Charlotte Ave	0.72	3200	F	96%	1%	1%	0%	2%	0%	С	0.089	F	0.563	3500	F	2007
5113) 6.14.161.67.176	02	To		0070	.,,		3rd St	_,,	0,0			•	0.000	0000	•	
		From					rlotte Ave									
5113) 3rd St	0.18	1300	F	96%	1%	1%	0%	2%	0%	F	0.089	F	0.682	1400	F	2007
<u> </u>		To				В	ath Ave									
		From	-			Delp	ohine Ave									
5114) Shenandoah Ave	0.58	810	F	97%	1%	1%	0%	0%	0%	С	0.105	F	0.637	880	F	2007
		To				Ki	rby Ave									
		From				SCL V	Vaynesboro	)								
5118) Delphine Ave	1.22	4400	F	88%	1%	1%	1%	8%	0%	С	0.096	F	0.567	4700	F	2007
		To					I-64									
5118) Delphine Ave	2.25	7600	F	92%	1%	2%	1%	5%	0%	С	0.084	F	0.511	8300	F	2007
5118) Delphine Ave	2.20	То		0 <u>2</u> 70	170		St US 250		070		7	•	0.011	0000	•	2001
		From					ohine Ave				i					
5119 Oak Lane	1.39	270	F	99%	1%	1%	0%	0%	0%	С	0.136	F	0.628	290	F	2007
5119) Oak Lane	1.00	To	·	0070	170		lhurst Ave	070	070		7	•	0.020	200	•	2001
		From	!								-					
Sherwood Rd	0.18		F	09%	0%	0%	man Pkwy 1%	0%	00/	С	0.101	F	0.603	1200	F	2007
Sherwood Rd	0.10	1100 _{To}	F	98%	U /0		Waynesboro		0%	U	0.101	I.	0.603	1200	Г	2007
		•	_								<del></del>					
Guilford Long	0.07	1100	<u> </u>	080/	00/		Bridge Rd		00/	F	0.101	E	0.675	1200	_	2007
Guilford Lane	0.07	1100	F	98%	0%	1%	0%	0%	0%	F	0.101	F	0.575	1200	F	2007
		To From				Har	npton Dr									
Guilford Lane	0.08	1600	F	98%	0%	1%	0%	0%	0%	С	0.096	F	0.506	1700	F	2007
$\overline{}$		To					Ivy St									
		From				Ro	sser Ave									
5122) Lew Dewitt Blvd	1.45	12000	F	98%	0%	1%	0%	1%	0%	С	0.088	F	0.508	12000	F	2007

# Virginia Department of Transportation Traffic Engineering Division 2007 Annual Average Daily Traffic Volume Estimates By Section of Route City of Waynesboro

						only of traymoodoro							
Route	Length	AADT	QA	4Tire	Bus	Truck 2Axle 3+Axle 1Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
ity of Wavnesboro		From:	1										
Dath Arra			ᄂ			2nd St		0.005	_		4.400	_	200
Bath Ave		1300 _{To-}	F			3rd St		0.085	F		1400	F	2007
			! -										
D 41 A		From:	L			3rd Street			_	0.00	050	_	000
Bath Avenue		250 To:	F			44.00		0.094	F	0.66	250	F	2007
						4th Street							
0 5.		From:				Greenbrier Rd			_			_	
Chatham Rd		190 To:	F					0.122	F		210	F	200
						Sunset Lane							
		From:				13th St							
Cherry Ave		190	F					0.101	F		210	F	200
		To:				14th St							
		From:				12th St							
Chestnut Ave		330	F					0.144	F		350	F	200
		To:				13th St							
		From:				SR 254							
Edward Avenue		300	F					0.130	F	0.582	300	F	200
		To:				Hickory Street							
		From				Hemlock St							
Florence Ave		1400	F					0.099	F		1500	F	2007
		To				Bridge Ave							
		From:				Bader St							
Monticello St		90	F					0.202	F		100	F	2007
		To:				Dead End							