

2008

**Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates**

where available

Special Locality Report

141

City of Bedford

Information in this report is included in Report

09

(Bedford County)

Prepared By

**Virginia Department of Transportation
Traffic Engineering Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is “R”, the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

 US Route

 Virginia State Route

 Frontage Road (F precedes frontage route number)

 Secondary Route

Special Routes

 Bus - Business Route
 Bypas - Bypass Route
 Truck - Truck Route
 ALT - Alternate Route
 Wye - Wye Route connector

 P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

 The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
Traffic Engineering Division
2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Bedford

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
43 South St	City of Bedford	0.96	1800	G	98%	1%	1%	0%	0%	0%	C	0.096	F	0.546	2000	G
43 South St	City of Bedford	0.14	1000	G	98%	0%	1%	0%	0%	0%	C	0.11	F	0.630	1100	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:		1700	G	98%	1%	1%	0%	0%	0%	0%	F	0.089	F	0.544	1900	G
43 South St	City of Bedford	0.06	650	G	98%	1%	1%	0%	0%	0%	F	0.121	F	0.779	700	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:		1600	G	97%	1%	1%	0%	0%	0%	0%	F	0.098	F	0.779	1800	G
43 Bus E Main St	City of Bedford	0.08	7100	G	98%	0%	1%	0%	1%	0%	F	0.094	F	0.501	7700	G
43 Bus N Bridge St	City of Bedford	0.16	6100	G	98%	1%	1%	0%	0%	0%	F	0.096	F	0.564	6600	G
43 Bus N Bridge St	City of Bedford	0.11	8400	G	98%	1%	1%	0%	0%	0%	C	0.093	F	0.543	9100	G
43 Peaks St	City of Bedford	0.62	3000	G	98%	0%	1%	0%	0%	0%	F	0.091	F	0.621	3300	G
43 Peaks St	City of Bedford	0.94	2700	G	98%	0%	1%	0%	0%	0%	C	0.090	F	0.611	2900	G
43 Talbot St	City of Bedford	0.05	720	G	97%	1%	1%	0%	0%	0%	F	0.096	F	0.503	780	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:		1700	G	98%	1%	1%	0%	0%	0%	0%	F	0.089	F	0.544	1900	G
43 Otey St	City of Bedford	0.14	980	G	97%	1%	1%	0%	0%	0%	C	0.091	F	0.7	1100	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:		1600	G	97%	1%	1%	0%	0%	0%	0%	F	0.098	F	0.779	1800	G
122 Burks Hill Rd	City of Bedford	0.54	10000	G	95%	1%	1%	1%	3%	0%	C	0.088	F	0.614	11000	G
122 460	City of Bedford (Maint: 09)	0.94	19000	G	87%	1%	1%	2%	9%	0%	F	0.081	F	0.581	20000	G
122 Independence Blvd	City of Bedford	1.02	10000	G	95%	1%	1%	1%	3%	0%	F	0.084	F	0.501	11000	G
122 Independence Blvd	City of Bedford	0.29	10000	G	95%	1%	1%	1%	3%	0%	C	0.087	F	0.545	11000	G
122 Independence Blvd	City of Bedford	0.50	9000	G	95%	1%	1%	1%	3%	0%	F	0.085	F	0.519	9800	G

Virginia Department of Transportation
Traffic Engineering Division
2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Bedford

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
122 Longwood Ave	City of Bedford	0.65	4400	G	94%	1%	1%	1%	4%	0%	C	0.087	F	0.627	4700	G
		To:														
122 Bus Crenshaw St	City of Bedford	0.96	5000	G	97%	1%	1%	0%	0%	0%	C	0.101	F	0.584	5400	G
		From:														
122 Bus Bus 221 460 W Main St	City of Bedford	0.19	6600	G	97%	1%	1%	0%	1%	0%	F	0.096	F	0.531	7200	G
		To:														
122 Bus 221 43 N Bridge St	City of Bedford	0.16	6100	G	98%	1%	1%	0%	0%	0%	F	0.096	F	0.564	6600	G
		From:														
122 Bus 221 43 N Bridge St	City of Bedford	0.11	8400	G	98%	1%	1%	0%	0%	0%	C	0.093	F	0.543	9100	G
		To:														
122 Bus 221 Longwood Ave	City of Bedford	0.71	7700	G	98%	1%	1%	0%	0%	0%	F	0.093	F	0.504	8400	G
		From:														
122 Bus 221 Longwood Ave	City of Bedford	0.47	9800	G	97%	1%	1%	0%	1%	0%	C	0.090	F	0.506	11000	G
		To:														
221 460	City of Bedford (Maint: 09)	0.67	20000	G	87%	1%	1%	2%	9%	0%	F	0.079	F	0.553	21000	G
		To:														
221 460	City of Bedford (Maint: 09)	0.33	6900	N	97%	1%	1%	0%	1%	0%	N	0.090	N	0.544	7400	N
		From:														
221 460	City of Bedford	0.68	6900	G	97%	1%	1%	0%	1%	0%	C	0.090	F	0.544	7400	G
		To:														
221 460 W Main St	City of Bedford	0.07	5600	G	97%	1%	1%	0%	1%	0%	F	0.096	F	0.528	6100	G
		From:														
221 Bus 460 122 W Main St	City of Bedford	0.19	6600	G	97%	1%	1%	0%	1%	0%	F	0.096	F	0.531	7200	G
		To:														
221 Bus 43 122 N Bridge St	City of Bedford	0.16	6100	G	98%	1%	1%	0%	0%	0%	F	0.096	F	0.564	6600	G
		From:														
221 Bus 43 122 N Bridge St	City of Bedford	0.11	8400	G	98%	1%	1%	0%	0%	0%	C	0.093	F	0.543	9100	G
		To:														
221 Bus 122 Longwood Ave	City of Bedford	0.71	7700	G	98%	1%	1%	0%	0%	0%	F	0.093	F	0.504	8400	G
		To:														

Virginia Department of Transportation
Traffic Engineering Division
2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Bedford

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
Bus 221 221 Longwood Ave	City of Bedford	0.47	9800	G	97%	1%	1%	0%	1%	0%	C	0.090	F	0.506	11000	G
221 Forest Rd	City of Bedford	0.68	6100	G	96%	1%	1%	1%	2%	0%	C	0.094	F	0.531	6600	G
460 221	City of Bedford (Maint: 09)	0.67	20000	G	87%	1%	1%	2%	9%	0%	F	0.079	F	0.553	21000	G
460	City of Bedford (Maint: 09)	0.18	16000	G	87%	1%	1%	2%	9%	0%	F	0.074	F	0.544	17000	G
460	City of Bedford (Maint: 09)	0.90	16000	G	87%	1%	1%	2%	9%	0%	F	0.074	F	0.544	17000	G
460 122	City of Bedford (Maint: 09)	0.94	19000	G	87%	1%	1%	2%	9%	0%	F	0.081	F	0.581	20000	G
460	City of Bedford (Maint: 09)	0.28	19000	G	87%	1%	1%	2%	9%	0%	F	0.079	F	0.538	20000	G
Bus 460 221	City of Bedford (Maint: 09)	0.33	6900	N	97%	1%	1%	0%	1%	0%	N	0.090	N	0.544	7400	N
460 221	City of Bedford	0.68	6900	G	97%	1%	1%	0%	1%	0%	C	0.090	F	0.544	7400	G
Bus 460 221 W Main St	City of Bedford	0.07	5600	G	97%	1%	1%	0%	1%	0%	F	0.096	F	0.528	6100	G
Bus 460 221 122 W Main St	City of Bedford	0.19	6600	G	97%	1%	1%	0%	1%	0%	F	0.096	F	0.531	7200	G
Bus 460 43 E Main St	City of Bedford	0.08	7100	G	98%	0%	1%	0%	1%	0%	F	0.094	F	0.501	7700	G
Bus 460 E Main St	City of Bedford	0.27	7100	G	98%	0%	1%	0%	1%	0%	F	0.094	F	0.554	7700	G
Bus 460 E Main St	City of Bedford	0.91	6500	G	98%	0%	1%	0%	1%	0%	C	0.094	F	0.564	7100	G
US 460, SR 122																

Virginia Department of Transportation
Traffic Engineering Division

2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Bedford

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail							
City of Bedford																
(F609) Dinwiddie Dr	0.09	140	R								NA			NA		07/10/2007
			From:	SR 122 Burks Hill Rd												
			To:	SCL Bedford												
(1) 4th St	0.20	10	G	98%	1%	0%	0%	0%	0%	F	0.261	F	0.667	10	G	2008
			From:	Bedford Ave												
			To:	College St												
(1) College St	0.14	1000	G	98%	1%	0%	0%	0%	0%	F	0.162	F	0.633	1100	G	2008
			From:	4th St												
			To:	SR 43 Peaks Street												
(2) Dawn Dr	0.63	1300	G	94%	1%	1%	1%	4%	0%	C	0.146	F	0.765	1400	G	2008
			From:	Park St												
			To:	Independence Blvd												
(3) Orange St	0.39	790	G	97%	1%	2%	1%	0%	0%	C	0.108	F	0.631	860	G	2008
			From:	Grove St												
			To:	Gold Rd												
(3) Orange St	1.47	890	G	97%	1%	2%	1%	0%	0%	F	0.110	F	0.544	970	G	2008
			From:	ECL Bedford												
(4) Ridge St/Otey St	0.27	350	G	96%	2%	1%	1%	0%	0%	F	0.128	F	0.557	380	G	2008
			From:	SR 43 South St												
			To:	SR 43 South St												
(5) Bridge St	0.07	1900	G	96%	2%	1%	1%	0%	0%	C	0.104	F	0.606	2100	G	2008
			From:	Washington St												
			To:	US 221, W Main St												
(6) Whitfield Rd	0.61	2100	G	99%	0%	0%	0%	0%	0%	C	0.087	F	0.509	2300	G	2008
			From:	SR 43 Peaks St												
			To:	Oakwood St												
(3050) Washington St	0.21	1500	G	98%	1%	1%	0%	0%	0%	C	0.106	F	0.564	1700	G	2008
			From:	W Main St												
			To:	Crenshaw St												
(3050) Washington St	0.25	1900	G	98%	1%	1%	0%	0%	0%	F	0.104	F	0.605	2000	G	2008
			From:	South St												
(3050) Washington St	0.07	1500	G	98%	1%	1%	0%	0%	0%	F	0.111	F	0.620	1600	G	2008
			To:	Otey St												
(3051) Link Rd	0.58	4300	G	96%	1%	1%	2%	1%	0%	C	0.096	F	0.544	4600	G	2008
			From:	SCL Bedford												
			To:	E Main St												
(3052) 4th St	0.15	5400	G	98%	1%	0%	0%	0%	0%	C	0.112	F	0.509	5900	G	2008
			From:	W Main St												
			To:	Bedford Ave												
(3052) Bedford Ave	0.10	4700	G	98%	1%	0%	0%	0%	0%	C	0.098	F	0.568	5000	G	2008
			From:	4th St												
			To:	2nd St												
(3052) Bedford Ave	0.20	4300	G	98%	1%	0%	0%	0%	0%	F	0.1	F	0.640	4700	G	2008
			From:	N Bridge St												
			To:	Grove St												
(3052) Jackson St	0.24	900	G								0.138	F	0.579	980	G	2008
			From:	Jackson St												
			To:	Orange St												
(3052) Grove St	0.28	1400	G	96%	0%	1%	1%	1%	0%	C	0.105	F	0.508	1500	G	2008
			From:	Grove St												
			To:	Grove St												
(3052) Orange St	0.08	1700	G	96%	0%	1%	1%	1%	0%	F	0.105	F	0.601	1900	G	2008
			From:	E Main St												
			To:	Orange St												
(3054) McGhee St	0.54	430	G	99%	0%	1%	0%	0%	0%	C	0.1	F	0.571	470	G	2008
			From:	Forest Rd												

Virginia Department of Transportation
Traffic Engineering Division

2008

Annual Average Daily Traffic Volume Estimates By Section of Route
City of Bedford

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail							
City of Bedford																
(3059) Park St	0.30	970	G	94%	1%	1%	1%	4%	0%	F	0.123	F	0.758	1000	G	2008
			From:	141-2 Gap Terminus Greenwood St						To:	US 221					
(3061) Oakwood St	0.59	3600	G	99%	0%	0%	0%	0%	0%	C	0.087	F	0.504	4000	G	2008
			From:	Longwood Ave						To:	Whitfield Rd					
Baltimore Ave	300		G								0.122	F	0.687	330	G	2008
			From:	Oak St						To:	Park St					
College St	750		G								0.178	F	0.551	750	G	2008
			From:	Bedford Ave						To:	Mountain Ave					
Pinecrest Ave	610		G								0.1	F	0.517	660	G	2008
			From:	Mayberry Dr						To:	Morgan St					
Shady Knoll Ave	540		G								0.11	F	0.587	580	G	2008
			From:	Longwood Ave						To:	Dawn Dr					