2002

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 223

Town of Glasgow

Prepared By

Virginia Department of Transportation Mobility Management Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Mobility Management Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT's Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

Peak Hour: The estimate of the traffic volume for the 30th highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North
81 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

(29) US Route

7 Virginia State Route

(600) Secondary Route

Special Routes

Bus Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
ALT ALT - Alternate Route
Wve - Wve Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

						I own of Glas	gow								
Route	Length	AADT	QA	4Tire	Bus	T 2Axle 3+Axl	ruck e 1Trail	2Trail	QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
Town of Glasgow				From:		WCL Glasgo	w	1							
130	1.60	3200	N	90%	2%	2% 2%	4%	1%	Ν	0.116	Ν	0.569	3200	Ν	2002
				To:		ECL Glasgo	V								
				From:		Dead End									
679	0.07	10	R							NA			NA		1998
				From:		81-1115									
679	0.06	150	R	To:		01 1105 NOD	TIL			NA			NA		07/16/20
				From:		81-1105 NOR 81-1105 SOU									
679	0.07	380	R							NA			NA		1998
81)				To:		WCL GLASG	OW								
$\widehat{}$				From:		Dead End									
684	0.50	100	R							NA			NA		1998
				From:		SR 130									
684	0.18	3600	G	92%	0%	2% 4%	2%	1%	С	0.105	F	0.650	3600	G	2002
				To: From:		81-783									
684 81	0.14	1900	G	92%	0%	2% 4%	2%	1%	F	0.1	F	0.601	2000	G	2002
<u> </u>				From:		81-1106		-							
(684)	0.26	1100	G	92%	0%	2% 4%	2%	1%	F	0.112	F	0.657	1100	G	2002
				To: From:		81-1104									
684 684	0.36	960	G	92%	0%	2% 4%	2%	1%	F	0.114	F	0.646	970	G	2002
<u> </u>				To:		WCL GLASG	OW								
	0.40	400	_	From:		81-1112									07/40/00
783	0.12	120	R							NA			NA		07/12/200
				From:		81-1114		-							
(7 <u>8</u> 3)	0.30	240	R							NA			NA		1998
783 783				From:		81-684									
783)	0.28	2200	R	Ter						NA			NA		07/16/200
				To:		81-1101									
	0.07	140	R	From:		81-1111				NA			NA		1998
784	0.07	140	K							INA			INA		1990
	0.06	280	R	From:		81-1110				NA			NA		07/12/200
(784)	0.00	200	K							INA			INA		07/12/200
	0.10	450		From:		SR 130				NIA			NΙΔ		1000
(784)	0.10	450	R							NA			NA		1998
$\overline{}$	0.07	440		From:		81-783				NIA			NIA		07/40/00
(784)	0.07	110	R	To:		81-1107				NA			NA		07/12/200
				From:		SR 130									
(926)	0.05	100	R			SK 130				NA			NA		07/12/200
826	0.00		•••	To:		01 1110									0.7.12/20
(026)	0.12	80	R	From:		81-1118				NA			NA		07/12/200
826	02			To:		Dead End									0.7.12/20
				From:		81-783									
1101	0.06	300	R	<u> </u>				•		NA			NA		1998
81				To		81-1107									
1101)	0.06	480	R	From:						NA			NA		07/12/200
1101				To		81-1106									
1101	0.12	1000	R	From:		01-1100				NA			NA		1998
81	· 			To		81-1115									
(1101)	0.06	500	R	From:		01-1113				NA			NA		07/12/200
(81)				To		01 1105				** *					
	0.06	60	R	From:		81-1105				NA			NA		1998
1101	0.00		••	To-		81-1104				, .					.000
				-											

					I own of Glasgow				
Route	Length	AADT	QA	4Tire	Bus 2Axle 3+Axle 1Trail 2Trail	QC Peak	QK Dir Factor	AAWDT (QW Year
Town of Glasgow				From:	81-1109				
1102	0.05	70	R		01 1107	NA		NA	07/12/200
				To: From:	81-1108				
1102	0.06	440	R			NA		NA	1998
	0.06	150	R	From:	81-783	NA		NA	07/12/200
1102	0.00	100		To	81-1107			101	011121200
1102	0.06	80	R	From:	_	NA		NA	1998
01)				To: From:	81-1106 Gap Terminus 81-1119 Gap Terminus				
1102	0.06	90	R		or responding	NA		NA	07/12/200
				From:	81-1115				
1102	0.06	180	R			NA		NA	1998
	0.06	350	R	From:	81-1105	NA		NA	07/12/200
1102	0.00			To:	81-1104	101		101	011121200
\sim				From:	SR 130				
1103	0.10	470	R			NA		NA	1998
	0.05	360	R	From:	81-1109	NA		NA	07/12/200
1103	0.00			To:	81-1108 Gap Terminus	101		101	011121200
$\overline{}$				From:	81-684				
1104	0.04	440	R	_		NA		NA	1998
	0.12	60	R	From:	81-1102	NA		NA	07/12/200
1104	0.12			To:	81-1101				01712/200
1104	0.13	70	R	From:	VI 11V1	NA		NA	07/12/200
				To: From:	81-1120				
1104	0.13	70	R			NA		NA	07/12/200
	0.20	20	R	From:	81-1117	NA		NA	1998
1104	0.20			To:	Dead End	101		101	1000
				From:	81-1102				
1105	0.12	190	R			NA		NA	07/12/2001
(1105)	0.13	380	R	From:	81-1101	NA		NA	1998
(1105)				To: From:	81-1120				
1105	0.12	460	R	From:		NA		NA	07/12/2001
				From:	81-1117				
(1105)	0.11	580	R	_		NA		NA	1998
(1105)	0.10	760	R	From:	81-1116	NA	 	NA	07/16/2001
1105				To:	81-679 SOUTH	<u> </u>			
1105	0.02	140	R	From:		NA		NA	1998
$\overline{}$				To: From:	81-679 NORTH				
(1105)	0.12	60	R	To:	FIRST STREET	NA		NA	07/16/2001
				From:	81-684				
1106	0.13	790	R	<u></u>	·- · · ·	NA		NA	1998
$\widehat{}$				To: From:	81-1102				
1106	0.12	730	R	To:	81-1101	NA		NA	07/12/2001
					01-1101				

Route	Length	AADT	QA	4Tire	BusTruck 2Axle 3+Axle 1Trail 2Trail		Dir Factor	AAWDT	QW	Year
Town of Glasgow				From:		1				
1107	0.10	60	R		81-1114	NA		NA		1998
ŔĨ				To:	81-784					
1107	0.17	180	R	rioni:		NA		NA		07/12/200
				To: From:	81-684]				
1107	0.14	460	R			NA		NA		1998
1107	0.12	210	R	From:	81-1102	NA		NA		07/12/200
	0.12	210	K	To:	81-1101]		INA		07/12/200
				From:	Dead End					
108	0.24	190	R			NA		NA		1998
	0.40	200		From:	81-1113	}		NIA		07/40/00
1108	0.12	260	R	. —		NA 1		NA		07/12/20
1108	0.12	220	R	From:	81-1112	NA		NA		1998
81 81				To:	81-1114	1				
1108	0.13	270	R	From:	01 1111	NA		NA		07/12/20
_				To: From:	81-784]				
1108	0.19	200	R		01.001.0	NA 1		NA		1998
				From:	81-684 Gap Terminus 81-1103 Gap Terminus					
1108	0.12	390	R		•	NA		NA		07/12/20
				To: From:	81-1102]				
1108	0.12	120	R	To:	Dead End	NA 1		NA		1998
				From:	81-1103	<u>!</u>				
1109	0.12	80	R		61-1103	NA NA		NA		07/12/20
ŘÍ.				To: From:	81-1102]				
1109	0.08	80	R			NA		NA		1998
<u>~~</u>				To: From:	Dead End	<u> </u>				
1110	0.25	220	R	FIOIII.	81-1112	J NA		NA		1986
1110				To:	81-784]				
1111				From:	81-1112					
	0.25	100	R	To:	81-784	NA 1		NA		07/12/20
				From:	Dead End					
1112	0.03	60	R	_		NA		NA		07/12/20
				To: From:	81-1111 Gap Terminus 81-1110 Gap Terminus					
112)	0.07	180	R		or-rivo dap reminus	NA NA		NA		1998
(1112)				To: From:	SR 130 Gap Terminus 81-1108 Gap Terminus					
1112)	0.07	100	R	<u> </u>	81-1108 Gap Terminus	NA		NA		07/12/20
1112				To:	81-783					
$\overline{}$	0.00	440	_	From:	SR 130					1000
1113	0.08	110	R			NA 1		NA		1998
1113	0.02	40	R	From:	81-1108	NA		NA		1986
1113	J.U2		• • •	To:	Dead End	1.7.				.500
				From:	81-1108					
1114	0.05	60	R			NA		NA		1998
1114	0.06	70	R	To: From:	81-783	NA		NA		07/12/20
		/11	ĸ			NA		NA		コフノコンバンハ

						0. 0.00,	,								
Route	Length	AADT	QA	4Tire	Bus 2A	Tr xle 3+Axle	uck 1Trail	2Trail	QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
Town of Glasgow								-							
\bigcirc	0.40	440	_	From:		81-1102									07/40/000
1115	0.12	140	R							NA			NA		07/12/2001
				To: From:		81-1101		-							
1115	0.25	500	R							NA			NA		1998
				To: From:		81-1117		-							
1115	0.09	240	R							NA			NA		07/16/2001
				To:		81-1116		ŀ							
1115	0.06	48	R							NA			NA		1998
81				To:		End; Gap Ten									
	0.40	70	_	From:	81-6	679 Gap Term	inus			N.1.A			NIA		07/40/000
1115	0.12	70	R	To		D1E-1				NA			NA		07/16/2001
						Dead End									
\bigcirc	0.07	210	R	From:		81-1115				NIA			NA		1998
1116	0.07	210	ĸ	To:		81-1105		1		NA			NA		1996
				From:				<u>.</u>							
	0.07	260	R			81-1115				NA			NA		07/16/200
1117	0.07	200	- 1	_						INA			INA		077107200
\bigcirc	0.00		R	From:		81-1105				NI A			NIA		4000
1117	0.06	50	ĸ	To:		81-1104				NA			NA		1998
				From:				l I							
	0.05	40	R	110		81-826				NA			NA		07/12/2001
1118	0.03	40	1	To:		Cul-de-Sac				INA			INA		01/12/2001
				From:		81-1102		1							
(1110)	0.13	100	R	<u> </u>		31-1102				NA			NA		07/12/2001
1119	5.10			To-		81-1101		ĺ							2.7.2.2001
				From:		81-1105		1							
(1120)	0.06	10	R	<u> </u>		31 1103				NA			NA		1998
1120		-		To:		81-1104									