

2012

**Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates**

where available

Special Locality Report

129

City of Salem

Information in this report is included in Report

80

(Roanoke County)

Prepared By

**Virginia Department of Transportation
Traffic Engineering Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is “R”, the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

 US Route

 Virginia State Route

 Frontage Road (F precedes frontage route number)

 Secondary Route

Special Routes

 Bus - Business Route
 Bypas - Bypass Route
 Truck - Truck Route
 ALT - Alternate Route
 Wye - Wye Route connector

 P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

 The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
Traffic Engineering Division
2012
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
11 460 West Main St	City of Salem	1.12	18000	G	96%	1%	1%	2%	2%	0%	F	NA			21000	G
11 460 West Main St	City of Salem	1.31	27000	F	98%	0%	1%	0%	0%	0%	F	0.079	F	0.507	30000	F
11 460 West Main St	City of Salem	0.60	14000	F	98%	0%	1%	0%	0%	0%	F	0.090	F	0.564	16000	F
11 460 West Main St	City of Salem	0.35	13000	F	98%	0%	1%	0%	0%	0%	F	0.081	F	0.528	15000	F
11 College Ave	City of Salem	0.09	2000	F	98%	0%	1%	0%	0%	0%	F	0.097	F	0.615	2200	F
11 College Ave	City of Salem	0.72	5500	F	98%	0%	1%	0%	0%	0%	F	0.102	F	0.536	6200	F
11 Colorado St	City of Salem	0.43	15000	F	98%	0%	1%	0%	0%	0%	F	0.09	F	0.583	17000	F
11 Apperson Dr	City of Salem	1.03	20000	F	98%	0%	1%	0%	0%	0%	F	0.091	F	0.53	22000	F
11 Apperson Dr	City of Salem	1.04	13000	F	98%	0%	1%	0%	0%	0%	F	0.085	F	0.504	15000	F
ALT 460 4th St	City of Salem	0.40	17000	F	96%	0%	1%	1%	1%	0%	F	0.087	F	0.546	18000	F
ALT 460 4th St	City of Salem	0.37	19000	F	96%	0%	1%	1%	1%	0%	C	0.09	F	0.528	20000	F
ALT 460 4th St	City of Salem	0.29	16000	G	96%	0%	1%	1%	1%	0%	F	NA			17000	G
ALT 460 4th St	City of Salem	0.28	9500	F	97%	0%	1%	0%	1%	0%	F	0.092	F	0.589	10000	F
ALT 460 Texas St	City of Salem	0.31	11000	F	97%	0%	1%	0%	1%	0%	C	0.099	F	0.604	11000	F
ALT 460 Texas St	City of Salem	0.61	6100	F	97%	0%	1%	1%	1%	0%	C	0.097	F	0.564	6500	F
ALT 460 Texas St	City of Salem	0.24	2700	F	97%	0%	1%	1%	1%	0%	F	0.106	F	0.965	2900	F

Virginia Department of Transportation
Traffic Engineering Division
2012
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW	
							2Axle	3+Axle	1Trail	2Trail							
ALT 11 ALT 460 419 Electric Rd	City of Salem	From: Texas St	0.53	21000	F	97%	0%	1%	1%	1%	F	0.1	F	0.59	22000	F	
		To: E Main St															
ALT 11 ALT 460 E Main St	City of Salem	From: SR 419 Electric Rd	0.44	15000	F	96%	1%	1%	1%	2%	0%	F	0.082	F	0.524	17000	F
		To: WCL Roanoke															
North 81	City of Salem (Maint: 80)	From: SCL Salem	0.20	26000	F	74%	1%	1%	1%	22%	2%	F	0.104	A	26000	F	
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:															
North 81	City of Salem (Maint: 80)	From: SR 112 Wildwood Rd	0.22	29000	A	79%	1%	1%	1%	17%	1%	F	0.098	A	29000	A	
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:															
South 81	City of Salem (Maint: 80)	From: NCL Salem	0.28	24000	G	78%	1%	1%	1%	18%	1%	C	0.110	A	24000	G	
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:															
South 81	City of Salem (Maint: 80)	From: SR 112 Wildwood Rd	0.14	28000	A	79%	1%	1%	1%	17%	1%	C	0.106	A	28000	A	
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:															
South 81	City of Salem (Maint: 80)	From: NCL Salem	0.90	28000	A	79%	1%	1%	1%	17%	1%	C	0.106	A	28000	A	
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:															
112 Wildwood Rd	City of Salem	From: US 11, US 460 Main St	0.44	18000	G	99%	1%	0%	0%	0%	F	NA		19000	G		
		To: NCL Salem															
311 Thompson Memorial Dr	City of Salem	From: College Ave	0.17	6900	F	98%	0%	1%	0%	1%	0%	F	0.105	F	0.603	7300	F
		To: Main St															
311 Thompson Memorial Dr	City of Salem	From: Rose Ln	0.94	11000	F	98%	0%	1%	0%	1%	0%	C	0.108	F	0.555	12000	F
		To: NCL Salem															
419 Electric Rd	City of Salem	From: SCL Salem	0.55	11000	F	98%	0%	1%	0%	1%	0%	F	0.107	F	0.545	12000	F
		To: US 11 Apperson Dr															
419 Electric Rd	City of Salem	From: Roanoke Boulevard	0.58	24000	F	99%	0%	0%	0%	0%	F	0.096	F	0.501	27000	F	
		To: NCL Salem															

Virginia Department of Transportation
Traffic Engineering Division
2012
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
419 Electric Rd	City of Salem	0.89	17000	F	97%	0%	1%	1%	1%	0%	C	0.095	F	0.601	18000	F
419 ALT US 460 Texas St	City of Salem	0.53	21000	F	97%	0%	1%	1%	1%	0%	F	0.1	F	0.59	22000	F
419 ALT 460 11 Electric Rd	City of Salem	0.88	16000	F	96%	0%	1%	1%	2%	0%	F	0.100	F	0.612	18000	F
419 NCL Salem	City of Salem	1.12	18000	G	96%	1%	1%	2%	2%	0%	F	NA			21000	G
460 11 West Main St	City of Salem	1.31	27000	F	98%	0%	1%	0%	0%	0%	F	0.079	F	0.507	30000	F
460 SR 112	City of Salem	0.60	14000	F	98%	0%	1%	0%	0%	0%	F	0.090	F	0.564	16000	F
460 ALT US 460, 4th St	City of Salem	0.35	13000	F	98%	0%	1%	0%	0%	0%	F	0.081	F	0.528	15000	F
460 Academy St	City of Salem	0.11	12000	F	96%	1%	1%	1%	2%	0%	F	0.084	F	0.523	13000	F
460 US 11 College Ave	City of Salem	0.29	14000	F	96%	1%	1%	1%	2%	0%	F	0.085	F	0.519	15000	F
460 SR 311 Thompson Memorial Dr	City of Salem	0.93	12000	F	96%	1%	1%	1%	2%	0%	F	0.082	F	0.548	13000	F
460 Lynchburg Tpke	City of Salem	0.24	14000	F	96%	1%	1%	1%	2%	0%	F	0.088	F	0.558	15000	F
460 Kessler Mill Rd	City of Salem	0.44	15000	F	96%	1%	1%	1%	2%	0%	F	0.082	F	0.524	17000	F
460 SR 419 Electric Rd	City of Salem	0.28	19000	F	96%	0%	1%	1%	1%	0%	F	0.087	F	0.546	18000	F
460 WCL Roanoke	City of Salem	0.37	19000	F	96%	0%	1%	1%	1%	0%	C	0.09	F	0.528	20000	F
460 W Main St US 11; 460	City of Salem	0.29	16000	G	96%	0%	1%	1%	1%	0%	F	NA			17000	G
460 Elm St	City of Salem	0.28	9500	F	97%	0%	1%	0%	1%	0%	F	0.092	F	0.589	10000	F
460 Union St	City of Salem	0.31	11000	F	97%	0%	1%	0%	1%	0%	C	0.099	F	0.604	11000	F
460 Colorado St	City of Salem	0.31	11000	F	97%	0%	1%	0%	1%	0%	C	0.099	F	0.604	11000	F
460 Roanoke Blvd	City of Salem	0.31	11000	F	97%	0%	1%	0%	1%	0%	C	0.099	F	0.604	11000	F
460 Idaho St	City of Salem	0.31	11000	F	97%	0%	1%	0%	1%	0%	C	0.099	F	0.604	11000	F

Virginia Department of Transportation
Traffic Engineering Division
2012
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
ALT 460 ALT 11 Texas St	City of Salem	0.61	6100	F	97%	0%	1%	1%	1%	0%	C	0.097	F	0.564	6500	F
ALT 460 ALT 11 Texas St	City of Salem	0.24	2700	F	97%	0%	1%	1%	1%	0%	F	0.106	F	0.965	2900	F
ALT 460 ALT 11 419 Electric Rd	City of Salem	0.53	21000	F	97%	0%	1%	1%	1%	0%	F	0.1	F	0.59	22000	F

Virginia Department of Transportation
Traffic Engineering Division

2012

Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail							
City of Salem																
(F70) Skyview Rd	0.02	560	R								NA			NA		07/10/2009
			From:	SR 112; 80-619 Litchell Rd												
			To:	Roanoke County Line												
(1) Market St	0.06	3000	F	99%	0%	0%	0%	0%	0%	C	0.087	F	0.556	3200	F	2012
			From:	Calhoun St												
			To:	US 11 West Main St												
(2) Idaho St	0.18	3300	N	99%	0%	0%	0%	0%	0%	N	0.091	N	0.527	3500	N	2012
			From:	ALT US 460 Texas St												
			To:	Illinois Ave												
(2) Idaho St	0.27	3300	F	99%	0%	0%	0%	0%	0%	F	0.091	F	0.527	3500	F	2012
			From:	Lynchburg Tpke												
(3) King St	0.07	140	F	99%	0%	1%	0%	0%	0%	F	0.199	F		150	F	2012
			From:	Front Ave												
			To:	Colorado St												
(4) Mill Lane	0.37	8500	F	98%	0%	0%	0%	1%	0%	C	0.086	F	0.517	9100	F	2012
			From:	W Riverside Dr												
			To:	W Main St												
(5) Piedmont Ave	0.10	5500	F	96%	0%	1%	2%	0%	0%	C	0.104	F	0.575	5800	F	2012
			From:	129-8051 Eddy Ave												
			To:	129-8002 Mulberry St												
(6) Green Ridge Rd	0.20	5600	F	99%	0%	0%	0%	0%	0%	C	0.11	F	0.574	6000	F	2012
			From:	SR 419 Electric Rd												
			To:	129-8018 Dalewood Ave												
(8002) Riverside Dr	0.40	5100	F	99%	0%	1%	0%	0%	0%	F	0.109	F	0.555	5400	F	2012
			From:	WCL Salem; 80-639 West Riverside Dr												
			To:	Mill Lane												
(8002) Riverside Dr	0.93	6300	F	97%	0%	1%	2%	0%	0%	F	0.116	F	0.543	6700	F	2012
			From:	Twelve OClock Knob Rd												
(8002) Riverside Dr	0.05	2900	N	97%	0%	1%	2%	0%	0%	N	0.092	N	0.555	3100	N	2012
			From:	Lucas St												
(8002) Piedmont Ave	0.20	5700	G	97%	0%	1%	2%	0%	0%	F	0.092	N	0.555	6100	G	2012
			From:	Mulberry St												
			To:	Piedmont Ave												
(8002) Mulberry St	0.19	2900	N	97%	0%	1%	2%	0%	0%	N	0.092	N	0.555	3100	N	2012
			From:	Front Ave												
			To:	Mulberry St												
(8002) Front Ave	0.65	2900	F	97%	0%	1%	2%	0%	0%	C	0.092	F	0.555	3100	F	2012
			From:	King Street												
(8004) Colorado St	0.29	2100	F	99%	0%	1%	0%	0%	0%	C	0.105	F	0.634	2200	F	2012
			From:	Roanoke Blvd												
			To:	Alt US 11, Alt US 460												
(8004) Colorado St	0.38	12000	F	99%	0%	1%	0%	0%	0%	F	0.087	F	0.564	13000	F	2012
			From:	US 11 Colorado St												
(8006) Roanoke Blvd	0.47	3200	F	99%	0%	1%	0%	0%	0%	F	0.093	F	0.622	3400	F	2012
			From:	South Market St												
			To:	Alt US 460												
(8008) Lynchburg Tpke	0.17	4000	F	99%	0%	1%	0%	0%	0%	F	0.085	F	0.552	4300	F	2012
			From:	US 460 E Main St												
			To:	129-2 Idaho St												
(8008) Lynchburg Tpke	0.67	1700	F	99%	0%	1%	0%	0%	0%	F	0.089	F	0.525	1800	F	2012
			From:	Alt US 460												
(8008) Lynchburg Tpke	0.25	5200	F	99%	0%	1%	0%	0%	0%	F	0.099	F	0.711	5600	F	2012
			From:	SR 419 Electric Rd												
			To:	ECL Salem												
(8008) Lynchburg Tpke	0.44	6100	F	97%	0%	1%	1%	1%	0%	C	0.093	F	0.585	6500	F	2012
			From:	ECL Salem												

Virginia Department of Transportation
Traffic Engineering Division

2012

Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail							
City of Salem																
(8010) Roanoke Blvd	0.41	8300	F	97%	0%	1%	1%	1%	0%	F	0.095	F	0.505	8900	F	2012
(8010) Roanoke Blvd	0.30	9400	F	99%	0%	1%	0%	0%	0%	C	0.100	F	0.503	10000	F	2012
(8010) Roanoke Blvd	1.30	11000	F	99%	0%	1%	0%	0%	0%	F	0.096	F	0.598	12000	F	2012
(8018) Dalewood Ave	0.55	1100	F	99%	0%	1%	0%	0%	0%	F	0.112	F	0.545	1200	F	2012
(8018) Green Ridge Rd	0.19	6000	F	99%	0%	1%	0%	0%	0%	F	0.106	F	0.571	6400	F	2012
(8037) Twelve O'Clock Knob Rd	0.98	1100	F	98%	0%	1%	0%	0%	0%	F	0.101	F	0.755	1200	F	2012
(8047) Diuguids Lane	0.09	4700	F	98%	0%	1%	0%	0%	0%	F	0.111	F	0.599	5000	F	2012
(8051) Eddy Ave	0.20	6500	F	98%	0%	1%	0%	0%	0%	F	0.106	F	0.620	6900	F	2012
(8051) Eddy Ave	0.18	4500	F	98%	0%	1%	0%	0%	0%	F	0.119	F	0.579	4800	F	2012
(8051) Union St	0.23	8200	F	98%	0%	1%	0%	0%	0%	C	0.089	F	0.551	8800	F	2012
(8051) Union St	0.46	2100	F	98%	0%	1%	0%	0%	0%	C	0.094	F	0.623	2200	F	2012
(8051) Academy St	0.64	1300	F	98%	0%	1%	0%	0%	0%	F	0.131	F	0.523	1400	F	2012
(8051) Academy St	0.51	1800	F	98%	0%	1%	0%	0%	0%	F	0.104	F	0.643	1900	F	2012
(8059) Goodwin Ave	0.72	2300	F	99%	0%	1%	0%	0%	0%	C	0.1	F	0.539	2500	F	2012
(8065) Kessler Mill Rd	1.65	1600	F	98%	0%	1%	0%	0%	0%	C	0.085	F	0.587	1800	F	2012
3rd St	190	F									0.102	F	0.705	200	F	2012
6th St	680	G										NA		720	G	2012
8th St	3500	F									0.109	F	0.584	3800	F	2012
Bonavista Rd	150	F									0.193	F	0.714	160	F	2012
Burwell St	1300	F									0.128	F	0.508	1400	F	2012

Virginia Department of Transportation
Traffic Engineering Division

2012

Annual Average Daily Traffic Volume Estimates By Section of Route
City of Salem

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail						
<u>City of Salem</u>															
Chapman St	340	F								0.139	F	0.529	360	F	2012
			From:	Burwell St											
			To:	2nd St											
Fletcher St	230	F								0.103	F	0.528	240	F	2012
			From:	Gardner Dr											
			To:	Howard Dr											
Goodwin Ave	1100	F								0.108	F	0.508	1200	F	2012
			From:	Logan St											
			To:	NCL Salem											
Jackson Dr	480	F								0.121	F	0.681	510	F	2012
			From:	Randolph Ave											
			To:	Kessling Ave											
Macon St	120	F								0.133	F	0.629	120	F	2012
			From:	Keesling Ave											
			To:	Randolph Ave											
Pearl St	170	F								0.137	F	0.588	180	F	2012
			From:	Carolina Ave											
			To:	Missouri Ave											
Texas Hollow Rd	2700	F								0.11	F	0.605	2900	F	2012
			From:	Valleydale Rd											
			To:	W Main St											
Virginia Ave	290	F								0.138	F	0.667	310	F	2012
			From:	Richfield Ave											
			To:	Fairview Ave											