### 2015

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

## Special Locality Report 117

City of Lexington

Information in this report is included in Report

81

(Rockbridge County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

#### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

#### **Publication Notes**

#### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

#### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

#### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

#### Route Shield Legend

#### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	

(F241)	Frontage Road (F precedes frontage route number)

(600) Secondary Route

Virginia State Route

#### Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

#### Virginia Department of Transportation Traffic Engineering Division 2015

### Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

		Oit,	or rexing	1011				Tru	ck			K		Dir		
Route	Jurisdiction	n Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	QW
	From:	SG	CL Lexington	n												
11 S Lee Highway	City of Lexing	ton 0.59	11000	G	97%	1%	1%	1%	1%	0%	С	0.091		0.507	12000	G
<u> </u>	To: From:		Main St				$\neg$ $\vdash$									
(11) N Lee Highway	City of Lexing	ton 0.04	11000	G	97%	1%	1%	1%	1%	0%	F	0.091		0.501	12000	G
<u>~</u>	To: From:		Bus US 11													
(11) N Lee Highway	City of Lexing		22000	G	97%	0%	1%	1%	1%	0%	F	0.100		0.612	24000	G
<del></del>	10:		CL Lexingto													
Bus 11 Main St	From L City of Lexing		CL Lexington 2900	n G	97%	1%	1%	0%	0%	0%	С	0.111		0 532	3100	G
11) Wall St	Gity of Lexing			<u> </u>	31 /6	1 /0	1 /0	0 /6	0 /6	0 /6	O	0.111		0.552	3100	u
Bus	From:		Thornhill Rd													
11 Main St	City of Lexing	ton 0.16	5000	G	97%	1%	1%	0%	0%	0%	F	0.101		0.672	5300	G
Bus	To: From:		Wallace St													
11 Main St	City of Lexing	ton 0.31	4800	G	97%	1%	1%	0%	0%	0%	F	0.093		0.593	5100	G
	To:		White St				$\neg$ $\vdash$									
Bus 11 Main St	City of Lexing	ton 0.31	3100	G	99%	0%	1%	0%	0%	0%	F	0.117			3300	G
(1) Main St	Combined Traffic Estimates for 2 Parallel F		5200	G	99%	0%	1%	0%	0%	0%	F	0.098	F	0.580	5500	G
	Tα		Nelson St				—									
Bus 11 Main St	From:L City of Lexing	ton 0.24	5700	G	99%	0%	1%	0%	0%	0%	_	0.092			6100	G
11 Wall St	Combined Traffic Estimates for 2 Parallel F			G	99%	0%	1%	0%	0%	0%	, F	NA				G
	To-				0070	0 70		0 70	0 70	0 70	•	1471			0000	ď
Bus	From:		Jefferson St													
(11) Main St	City of Lexing	ton 0.37	9500	G	99%	0%	1%	0%	0%	0%	F	0.090		0.512	10000	G
Bus	To: From:		Letcher St													
11 Main St	City of Lexing		9900	G	99%	0%	1%	0%	0%	0%	С	0.095		0.544	11000	G
<u> </u>	To:	US 11 N Lee			ghway											
Bus 11 Jefferson St	From L City of Lexing		US 11 Main		99%	0%	1%	0%	0%	0%	F	0.112			2200	G
Jefferson St	Combined Traffic Estimates for 2 Parallel F		2100 5200	G G	99% 99%	0% 0%	1%	0% 0%	0% 0%	0% 0%	F	0.112	F	0 580		G
	Tol	<u> </u>			33 /6	0 /6	1 /6	0 /6	0 /6	0 /6	'	0.030	'	0.500	3300	u
Bus	From:		60 Nelson													_
Jefferson St	City of Lexing		3300	G	99%	0%	1%	0%	0%	0%	С	0.09				G
	Combined Traffic Estimates for 2 Parallel F		<b>8900</b> US 11 Main	G	99%	0%	1%	0%	0%	0%	F	NA		0.501 12000  0.612 24000  0.532 3100  0.672 5300  0.593 5100  0.580 5500  6100 9500  0.512 10000	G	
	From:		CL Lexingto													
Nelson St	L City of Lexing		4200	G	98%	0%	1%	1%	0%	0%	С	0.094		0.628	4400	G
			Borden Rd													
60 Nelson St	From: L City of Lexing		5800	G	98%	0%	1%	1%	0%	0%	F	0.094		0.539	6100	G
	To:		lasgow Stree	et												

5/3/2016 7

#### Virginia Department of Transportation Traffic Engineering Division 2015

#### Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru 3+Axle	-		QC	K Factor	QK	Dir Factor	AAWDT	QW
-	From:	G	lasgow Stre	et												
(60) Nelson St	City of Lexington	0.20	5700	G	98%	0%	1%	1%	0%	0%	F	0.093		0.564	6000	G
<u> </u>	To		C2US 11-P				<u> </u>									
(60) Nelson St	City of Lexington	0.11	7600	G	98%	0%	1%	1%	1%	0%	F	0.089		0.549	8000	G
<u> </u>	To	Ra	ındolph Stre	et			<u> </u>									
(60) Nelson St	City of Lexington	0.21	6900	G	98%	0%	1%	1%	1%	0%	F	0.089		0.549	7300	G
<u> </u>	T <sub>C</sub>	Si	potswood D	)r			$\neg$ $\vdash$									
60 Nelson St	City of Lexington	0.35	13000	G	98%	0%	1%	1%	1%	0%	С	0.091		0.554	14000	G
	Τo:	ECL L	exington at	US 11												
	From:	WCL Lexington														
(251) Thornhill Rd	City of Lexington	0.38	5200	G	97%	0%	1%	1%	1%	0%	С	0.098		0.663	5600	G
	To:		Link Rd													
	From:	7	Thornhill Rd	i												
(251)Link Rd	City of Lexington	0.24	4500	G	97%	0%	1%	1%	1%	0%	F	0.093		0.639	4800	G
	To:		Main St													

5/3/2016

## Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

						City of Lexino	iton							
Route	Length	AADT	QA	4Tire	Bus	Tr 2Axle 3+Axle			QC	K Factor	QK Dir Factor	AAWDT	QW	Year
City of Lexington		From				Lewis St								
1 Diamond St	0.36	1400 <sub>To</sub>	G	98%	0%	1% 0% Main St	0%	0%	С	0.158	0.641	1500	G	2015
		From								1				
2 Lee St	0.08	<b>2000</b>	G	97%	1%	Nelson St 1% 1% Washington S	0%	0%	С	0.1	0.53	2100	G	2015
		From				Link Rd								
Thornhill Rd	0.38	<b>2100</b>	G	99%	0%	0% 0% Main St	0%	0%	С	0.102	0.762	2300	G	2015
4252) Enfield Rd	0.43	From 1400	G	99%	0%	WCL Lexingto	on 0%	0%	F	0.096	0.522	1500	G	2015
7232)		To				Lime Kiln Ro	i							
O		From				Enfield Rd								
Lime Kiln Rd	0.32	2000 <sub>то</sub>	G	99%	0%	0% 0%  McLaughlin S	0% St	0%	С	0.093	0.528	2200	G	2015
		From				WCL Lexingto	on							
Ross Rd	0.31	1200	G	99%	0%	1% 0%	0%	0%	F	0.108	0.711	1300	G	2015
$\smile$		To From				Jackson Ave								
Jackson Ave	0.27	1600	G	99%	0%	Ross Rd 1% 0%	0%	0%	С	0.132	0.653	1700	G	2015
Jackson Ave	0.21	To To		JJ /0	J /0	White St	0 /0	J /0		0.102	0.000	1700	u	2010
		From				SCL Lexingto	m			$\dashv$				
Houston St	0.40	2100	G	99%	0%	1% 0%	0%	0%	С	0.11	0.511	2300	G	2015
<u> </u>		From				Taylor St				<u> </u>				
Houston St	0.15	2400 <sub>To</sub>	G	99%	0%	1% 0%	0%	0%	F	0.106	0.502	2500	G	2015
						Main St								
	0.05	From	<u> </u>	000/	00/	Main St		00/			0.700	000	_	0045
McDowell St	0.05	340 To	G	98%	0%	1% 0% Jefferson St	0%	0%	С	0.126	0.729	360	G	2015
			<u> </u>							1				
Malker Ct	0.40	From	<u> </u>	000/	00/	Houston St	00/	00/	С	0.107	0.516	2000	0	2015
4257 Walker St	0.40	2600 To	G	98%	0%	1% 1% Nelson St	0%	0%	C	0.107	0.516	2800	G	2015
Oroston Ct	0.05	From	<u> </u>	000/	00/	Main St	00/	00/		0 101	0.070	0100	0	2015
4258 Preston St	0.05	1900 <sub>To</sub>	G	98%	0%	1% 0%	0%	0%	F	0.101	0.873	2100	G	2015
						Jefferson St				_				
Honny Ct	0.05	From	<u> </u>	000/	0%	Main St 1% 0%	0%	00/	С	0.100	0.624	1200	C	2015
4260 Henry St	0.05	1100 <sub>To</sub>	G	98%	0%	1% 0% Jefferson St		0%	C	0.100	0.624	1200	G	2015
		From												
4261) Lewis St	0.08	3900	G	98%	0%	Nelson St 1% 1%	0%	0%	С	0.11	0.590	4100	G	2015
Lewis St	0.00	3900 To		30 /6	0 78	Washington S		0 /6			0.590	4100	u	2010
		From				Lewis St	,,,			+				
4261) Washington St	0.30	3500	G	98%	0%	1% 1%	0%	0%	F	0.094	0.501	3800	G	2015
$\bigcup$		То				Main St								
4261) Washington St	0.06	3800 From	G	98%	0%	1% 1%	0%	0%	F	0.097	0.664	4000	G	2015
		To			-	Jefferson St		-		<u> </u>				
4261) Washington St	0.06	5000 From	G	98%	0%	1% 1%	0%	0%	F	0.091	0.58	5300	G	2015
Washington St	0.00			0070	0 70		0 70	0 70		0.001	0.00	0000	ď	2010
Maabinatan Ct	0.01	From	<u> </u>	000/	00/	Lee St	00/	00/			0.050	0500		0015
Washington St	0.21	3300 <sub>то</sub>	G	98%	0%	1% 1%	0%	0%	F	0.086	0.652	3500	G G G G G G G G G G G G G G G G	2015
			L			Nelson St								
Pardan Dd	0.04	From	<u> </u>	000/	00/	WCL Lexingto		00/			0.004	1000	0	0015
4262) Borden Rd	0.34	1100 To	G	98%	0%	1% 0%	0%	0%	С	0.099	0.621	1200	G	2015
						Nelson St								
O Lauria Ct	0.00	From	<u> </u>	000/	00/	Washington S		00/			0.540	1000	_	0015
4263 Lewis St	0.33	1500	G	98%	0%	1% 1%	0%	0%	С	0.143	0.543	1600	G	2015
		To	1			Diamond St								

5/3/2016 9

# Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

						Oity O	LOXING	011								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
City of Lexington																
		From					ouston St									
(4266) Spottswood Dr	0.40	2800	G	98%	0%	1%	0%	0%	0%	С	0.105		0.538	3000	G	2015
$\overline{}$		To				N	elson St								GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG	
		From:				Jef	ferson St									
(4267) White St	0.18	1500	G	98%	0%	1%	0%	0%	0%	F	0.106		0.641	1600	G	2015
		To:					aughlin St									
O 14 1 1 1 2		From:					Vhite St									
(4267) McLaughlin St	0.28	1900	G	99%	0%	1%	0%	0%	0%	С	0.103		0.681	2100	G	201
		From:					asgow St									
(4267) Glasgow St	0.06	1000	G	99%	0%	1%	aughlin St 0%	0%	0%	С	0.128	0.79	1100	G	2015	
(4267) Glasgow St	0.00	To:	G	33 /6	0 76		elson St	0 /6	0 76		0.120		0.73	1100	G G G G G G	2013
0		From:		000/	00/		orkle Drive		00/				0.507	4000	0	0045
Campbell Lane		1300 To:	G	98%	0%	1%	0%	0%	0%	С	0.126		0.507	1300	G	2015
							US 11									
		From:				Jac	kson Ave									
Edmondson Ave		370	G								0.169		0.618	370	G	2015
		To:				N	Main St								0 G 0 G 0 G 0 G 0 G 0 G	
		From:				W	allace St									
Taylor St		1400	G								0.137		0.646	1500	G	2015
		To:				Но	ouston St									
		From:				Was	hington St									
Tucker St		410	G								0.109		0.533	440	G	2015
		To:				M	lassie St								G G G G G G G	
		From				US	11 Main St									
Waddell St		1400	G	93%	3%	2%	1%	1%	0%	С	0.173		0.682	1400	G	2015
		To					allace St	.,.			$\exists$				-	2010
		From:					ferson St				1					
White St		3500	G	99%	0%	0%	0%	0%	0%	С	0.108			3500	G	2015
WINC Of		To:	<u> </u>	JJ /0	0 /0		Main St	0 /0	0 /0		3.100			0000	ч	2013
						ľ	vialli St								G G G G G G	

5/3/2016 10