### 2015

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

## Special Locality Report 140

Town of Abingdon

Information in this report is included in Report

95

(Washington County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

#### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

#### **Publication Notes**

#### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

#### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

#### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

#### Route Shield Legend

#### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	


(F241)	Frontage Road (F precedes frontage route number)


(600) Secondary Route

#### Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

Virginia State Route





#### Virginia Department of Transportation Traffic Engineering Division 2015

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

			n of Abingo					Tru	ıck			K		Dir		
Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK F	actor	AAWDT	QV
	From:	W	CL Abingdon	1			27 15(10	017000	TTTGII	Ziiaii		1 40101	•	uotoi		
11 19 Main St	Town of Abingdo	lon 0.55	7800	G	95%	1%	1%	2%	2%	0%	F	0.093	(	0.631	8100	G
$\rightarrow$ $\bigcirc$	To	SR 14	40 Jonesboro	Rd												
11) (19) Main St	Town of Abingdo		24000	G	98%	0%	1%	0%	0%	0%	F	0.094	(	0.535	25000	G
	To		Colonial Rd													
11 (19) Main St	From: Town of Abingdo		23000	G	98%	0%	1%	0%	0%	0%	F	0.093		0.507	24000	(
11) (19)						0,0		0 / 0	0 70	0 / 0	•	0.000		0.00.		
11 Main St/Lee Hwy	From: Town of Abingdo		Porterfield F	G G	98%	0%	1%	0%	0%	0%	F	0.087		0.51	15000	(
11 Main St/Lee Hwy	Town of Abiliga	1011 0.47	14000	G	90%	0%	1 70	0%	076	0%	Г	0.067		0.51	13000	
~~ <u>.</u>	To:		Palmer St													
11 Main St	Town of Abingd		15000	G	98%	0%	1%	0%	0%	0%	С	0.087	(	0.502	16000	C
ALT	To: From:		LT 58, Russel LT 58, Russel													
11 58 Main St	 Town of Abingd		12000	G	98%	0%	1%	0%	0%	0%	F	0.081	(	0.509	12000	
11) (36) 1114111 01	- F					0 70		070	0 70	070	•	0.001	,	0.000	12000	Ì
~~~ Main Ot/Leas Hissa	To From		, SR 75, Cum			40/		00/	00/	00/	_	0.004		0 575	40000	,
11 Main St/Lee Hwy	Town of Abingdo	lon 0.66	12000	G	99%	1%	0%	0%	0%	0%	F	0.084	(	0.575	13000	(
<u></u>	To: From:		Tanner St													
11 Main St/Lee Hwy	Town of Abingdo	lon 0.93	14000	G	99%	1%	0%	0%	0%	0%	F	0.085	(	0.528	15000	(
~	To	Т	Thompson Dr													
11 Main St/Lee Hwy	Town of Abingdo		19000	G	99%	1%	0%	0%	0%	0%	F	0.095	(	0.557	21000	(
~	Tα	I	Hillman Hwy													
11 Main St/Lee Hwy	From: Town of Abingdo		17000	G	99%	1%	0%	0%	0%	0%	С	0.094	(	0.561	18000	
11)	To:		CL Abingdon		0070	. , 0		0 / 0	0 70	0 / 0	Ū	0.00			.0000	•
	From:	W	CL Abingdon	1												
19 (11) Main St	Town of Abingd		7800	G	95%	1%	1%	2%	2%	0%	F	0.093	(	0.631	8100	(
19) (1)								_,,			-					
Moin St	Town of Abjoard		40 Jonesboro <b>24000</b>		000/	0%	10/	0%	0%	09/	F	0.094		0 525	25000	-
19 (11) Main St	Town of Abingdo	1011 0.43	24000	G	98%	0%	1%	0%	0%	0%	Г	0.094	,	0.535	25000	C
~ ~	To: From:		Colonial Rd													
19) (11) Main St	Town of Abingd		23000	G	98%	0%	1%	0%	0%	0%	F	0.093	(	0.507	24000	G
~ ~	To: From:		S 11 Main St Main St; Lee													
19 Porterfield Hwy	 Town of Abingd		16000	G	95%	0%	1%	1%	3%	0%	F	0.089		0.528	17000	(
19 T Official Tiwy	Town of Abingo	0.40		<u> </u>	33 /6	0 70	1 /0	1 /0	0 /0	0 70	'	0.000	•	0.020	17000	`
ALT	To: From:		Alt US 58													
19 58 Porterfield Rd	Town of Abingdo	lon 0.21	22000	G	95%	0%	1%	1%	3%	0%	F	0.091		0.56	23000	(
$\sim$	Tor	N	CL Abingdon	1												
	From:	Se	CL Abingdon													
58 (81)	Town of Abingdon (Ma				S	ee I-81	for direc	ctional tr	affic vo	lume es	timate	es for this	segme	ent.		
	Combined Traffic Estimates for 2 Parallel Ro		44000	Α	80%	1%	1%	1%	17%	1%		0.096	Α (		45000	Δ
	To:	,	SR 75								-					

5/3/2016 7

#### Virginia Department of Transportation Traffic Engineering Division 2015

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

Devite	Lord and taken				4.T.	D		Tru	ıck			K	01/	Dir	AANADT	014
Route	Jurisdiction	n Length	AADT	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	Q۷
$\sim$	From:	Mainta 05) 1 00	SR 75			1 04	for all or	-4114-	- cc:	l						
58 81	Town of Abingdon (		45000	_							timate	es for this	U		47000	_
	Combined Traffic Estimates for 2 Parallel F		45000 CL Abingd	G	80%	1%	1%	1%	17%	1%	F	0.081	F	0.521	47000	G
A.I. T.	From:															
ALT 58 19 Porterfield Rd	Town of Abing		CL Abingd 22000	G G	95%	0%	1%	1%	3%	0%	F	0.091		0.56	23000	G
36) (19)	Та		9 Porterfield					.,,		-,-						
ALT	From:															
58 Russell Rd	Town of Abing		8500	G	99%	0%	1%	0%	0%	0%	С	0.093		0.51	9000	(
ALT	From:		Valley Stree Valley St	et												
58 11 Main St	Town of Abing	gdon 0.24	12000	G	98%	0%	1%	0%	0%	0%	F	0.081		0.509	12000	(
$\sim$	To:		Main St													
ALT Cummings St	From:	ndon 0.70	US 11		000/	00/	10/	00/	10/	00/	0	0.005		0.500	10000	(
58 75 Cummings St	Town of Abing ταΓ	gdon 0.78	17000 I-81	G	98%	0%	1%	0%	1%	0%	С	0.085		0.529	18000	(
	From	COL AL														
75 Green Spring Rd	Town of Abing		ingdon Cou 8200	G	97%	0%	0%	1%	1%	0%	С	0.09		0.616	8700	(
75) G. Go.: Spg 1.G	Τα:		l Commerce		0.70	0,70		. , 0	. , 0	0,70	Ū	0.00		0.0.0	0.00	
→ ALT	From:		I-81													
75 58 Cummings St	Town of Abing		17000	G	98%	0%	1%	0%	1%	0%	С	0.085		0.529	18000	(
	10.		S 11 Lee H													
North (Table 1)	From: L Town of Abingdon (		CL Abingde 22000	on A	79%	1%	1%	1%	100/	1%	С	0.004			22000	ļ
81 (58)	Combined Traffic Estimates for 2 Parallel I			A	79% 80%	1%	1%	1%	18% 17%	1%	С	0.094 0.096	Α	0.511	45000	,
	Combined Trainic Estimates for 2 Faraner i				00%	1 70	1 70	1 70	1770	1 70	C	0.096	А	0.511	43000	,
Vorth	To- From:		75 Cummin	gs St												
81) (58)	Town of Abingdon (		23000	G	79%	1%	1%	1%	18%	1%	F	0.085			24000	C
$\circ \circ$	Combined Traffic Estimates for 2 Parallel I	•		G	80%	1%	1%	1%	17%	1%	F	0.081	F	0.521	47000	(
	To:		CL Abingd													
South	From:		CL Abingdo		0.10/	40/		40/	450/	40/	•	0.400			00000	
81 (58)	Town of Abingdon (	•	22000	A	81%	1%	1%	1%	15%	1%	С	0.102		0.544	22000	/
	Combined Traffic Estimates for 2 Parallel I	Roadways on this Route:	44000	Α	80%	1%	1%	1%	17%	1%	С	0.096	Α	0.511	45000	-
outh	To: From:	SR	75 Cummin	gs St												
81) (58)	Town of Abingdon (	Maint: 95) 0.79	22000	G	81%	1%	1%	1%	15%	1%	F	0.08			23000	(
$\circ \circ$	Combined Traffic Estimates for 2 Parallel I	Roadways on this Route:	45000	G	80%	1%	1%	1%	17%	1%	F	0.081	F	0.521	47000	(
	Tα:	N	CL Abingd	on												
	From:		CL Abingdo													
140 Jonesboro Rd	Town of Abing		20000	G	95%	0%	1%	1%	3%	0%	С	0.084		0.504	21000	C
$\sim$	To:	J	S 11 Main	St												

5/3/2016

### Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

						rown (	or Abingo	ion								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
own of Abingdon																
○ \#\ 00 B	0.00	From	<u> </u>			SR 140	Jonesboro	Rd					0.004	0000	_	0045
1 VHCC Dr	0.63	<b>2600</b>	G		τ	2 1 D	1: 3/11/	IC D			0.122		0.904	2600	G	2015
					ŀ		arking; VHC									
O 5	0.40	From:	<u> </u>			140-	1 VHCC D	•					0.050	4000	_	0045
2 Partnership Circle	0.10	1800 <sub>To:</sub>	G					¥ .			0.125		0.956	1800	G	2015
			<u> </u>				lege Parkin									
O Manadala Dal	4.07	From	<u> </u>	000/	40/		L Abingdon		00/				0.500	4400	0	0045
3 Wyndale Rd	1.07	3800 To:	G	98%	1%	0%	1%	0%	0%	С	0.098		0.593	4100	G	2015
						US	11 Main St									
		From				US	11 Main St				<u></u>				_	
4 Thompson Dr	0.19	5200	G								0.140		0.663	5200	G	2015
		To				S	tanley St									
		From	L			140-30	003 Valley	St							_	
6 Court St	0.08	1400	G								0.116		0.746	1500	G	2015
<u> </u>		To	<u> </u>			US	11 Main St									
_	0.08	From					Hwy; W M									
Cummings St		6600	G	99%	0%	0%	0%	0%	0%	F	0.092		0.538	7000	G	201
<u> </u>		To					/alley St									
Valley St		From:				Russel	l Rd; ALT	58								
	0.72	9100	G	99%	0%	0%	0%	0%	0%	С	0.101		0.518	9700	G	201
<u> </u>		To				(	Court St				$\neg$ —					
Valley St	0.14	6600 From	G	99%	0%	0%	0%	0%	0%	F	0.109		0.614	7000	G	2015
1000		To					tes Mill Rd				$\overline{}$					
		From				LIS	11 Main St									
Tanner St	0.08	1500	G	98%	1%	0%	0%	0%	0%	F	0.088		0.544	1500	G	2015
0004)		T													Ŭ.	
Whitee Mill Pd	0.97	2600	G	000/	10/		/alley St	00/	09/	С	0.005		0.507	2700		2015
Whites Mill Rd	0.87	2600 <sub>To</sub>		98%	1%	0%	0% ICL Abingd	0%	0%		0.085		0.597	2700	G	2015
	4.05	From	<u> </u>	000/	00/		1; Lee Hwy		00/				0.500	4700	0	004
Hillman Hwy	1.35	4400 To.	G	99%	0%	0%	0%	0%	0%	С	0.098		0.599	4700	G	2015
<u> </u>						ECL	_ Abingdon									
		From					5 Hillman I								_	
3006 Tunnel St/Old Saltwo	rks K0d08	1700	G	98%	1%	0%	0%	0%	0%	F	0.097		0.714	1800	G	2015
<u> </u>		To			95.	-740 JB-1	40 NCL A	oingdon								
		From:				Saw	grass Circle									
Augusta Dr		420								0.113		0.663	450	G	2015	
		To				Wir	nterham Dr									
		From:				P	reston St									
Bradley St		1300	G								0.123	0.643	1400	G	2015	
		To				I	Fuller St									
		From				В	Bogey Dr									
Fairway Dr		430	G				-				0.105		0.619	460	G	2015
<u> </u>		To				D	ead End									
<u> </u>		From:				Н	illside Dr									
Oak Hill St		260	G										0.5	270	G	2015
		To	ŕ			Stone	wall Height	S			0.129					
						Storie		-								

5/3/2016 9