2019

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 248

Town of Keysville

Information in this report is included in Report

19

(Charlotte County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
$\overline{}$		

Frontage Road (F precedes frontage route number)

(600) Secondary Route

Special Routes

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

Virginia State Route

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2019

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Keysville

Route	Jurisdiction	Longth	AADT	^^	4Tiro	Puo		Tru	ıck		QC	K	QK	Dir	A A M/DT	OW
noute	Junsaiction	Length	AADT	QA	4Tire	bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDI	QVV
Bus Bus	From:		Keysville													
(15)(360)	Town of Keysville (Maint: 19)	0.73	1400	N	93%	1%	1%	1%	5%	0%	Ν	0.110	F	0.579	1400	N
Bus Bus	To: From:	\$	S SR 40													
15 360 40 McDonald Rd	Town of Keysville (Maint: 19)	0.56	5600	G	93%	1%	1%	1%	5%	0%	F	0.092	F	0.548	5500	G
Bus Bus	Tow From:	1	N SR 40													
15 (360) Four Locust Hwy	Town of Keysville (Maint: 19)	0.37	5100	G	93%	1%	1%	1%	5%	0%	F	0.086	F	0.534	5000	G
	To:	To: CL Keysville														
	From:	WC	L Keysville	е												
(40) Church St	Town of Keysville (Maint: 19)	0.54	2900	N	89%	2%	1%	3%	6%	0%	N	0.113	F	0.566	2900	N
Bus Bus	To: From:		15, Bus US US 15 BUS													
(40) (15) (360) McDonald Rd	Town of Keysville (Maint: 19)	0.56	5600	G	93%	1%	1%	1%	5%	0%	F	0.092	F	0.548	5500	G
40 (13) (300)	To:		JS 15 BUS	-												
	From:	US 15, US 3		Keysvil												
(40) Lunenburg Hwy	Town of Keysville (Maint: 19)	0.40	3200	G	89%	2%	1%	1%	7%	0%	F	0.101	F	0.694	3200	G
	10:		L Keysville													
	From:		L Keysville										_			
59	Town of Keysville (Maint: 19)	0.58	1500 40 Keysville	N	93%	2%	1%	1%	3%	0%	N	0.087	F	0.538	1500	N
	From			e												
Bus Bus (360) (15)	Town of Keysville (Maint: 19)	0.73	Keysville 1400	N	93%	1%	1%	1%	5%	0%	Ν	0.110	F	0.579	1400	N
But But	Too From	,	S SR 40				\Box \vdash									
Bus Bus (360) (15) (40) McDonald Rd	Town of Keysville (Maint: 19)	0.56	5600	G	93%	1%	1%	1%	5%	0%	F	0.092	F	0.548	5500	G
Bus Bus	To: From:	1	N SR 40													
(360) (15) Four Locust Hwy	Town of Keysville (Maint: 19)	0.37	5100	G	93%	1%	1%	1%	5%	0%	F	0.086	F	0.534	5000	G
	To:	CL	Keysville		-										5500 5000 2900 5500 3200 1500 5500	

4/16/2020 7

Virginia Department of Transportation Traffic Engineering Division 2019 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Keysville

Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle	-		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Kevsville		Fron	1.				Keysville									
629 Southern Dr	0.24	200	R			SCL	Keysville				NA			NA		06/12/2018
(19)		Te	٦.			US 15 I	Bus NORT	H								
		Fron	r:			WCL	Keysville	:			<u> </u>					0=1101001
688 Blue Stone Rd	0.07	160	R		SD 40 CF	weah St. C	George Wa	chinatan l	Llww,		NA			NA		05/19/201
		Fron	1		3K 40 CI		s US 15	simigion	ıwy							
(712) Church St	1.02	680	R			Du	8 US 13				NA			NA		05/07/201
Church St		Te				NCL	Keysville									
_		Fron	1:		1	9-712 Hor	seshoe Be	nd Rd								
714 Railroad Ave	0.10	420	R								NA			NA		05/19/201
		T. Fron	2: 1:			19-71	6 Farrar S	t			_					
714 Railroad Ave	0.02	300	R								NA			NA		05/19/201
199		Te):			De	ad End									
O 101		Fron	1:			De	ad End				<u>ا </u>					00/07/00/
7 ₁₅) J St	0.06	7	R								NA			NA		06/07/201
O 12		Fron				19-757	Osborne	St]					
(7 _{1,5}) J St	0.07	500	R				XXC 15				NA			NA		06/07/201
							s US 15									
716) Farrar St	0.35	470	"L			19-714 1	Railroad A	ve			 NA			NA		06/07/201
716 Farrar St	0.55	470												INA		00/07/201
716) Farrar St	0.20	390 From	R		19	9-712 Hor	seshoe Be	nd Rd			NA			NA		06/07/201
716) Farrar St	0.20	39U Tr	, n			De	ad End							IVA		06/07/201
		Fron	r:				s US 15									
718) H St	0.08	1100	R			Du	8 03 13				NA			NA		06/07/201
199		Te):	19-712 Horseshoe Bend Rd												
		Fron	1.			De	ad End									
722 Spaulding Ave	0.07	290	R								NA			NA		06/07/201
19		T _e Fron	Y			19-757	Osborne	St			_					
722 Spaulding Ave	0.05	1000	R								NA			NA		06/07/201
19		Te):			Bu	s US 15									
O 5 o.		Fron		 /	121		Osborne		221					450		2212
731 Pettus St	0.07	160	G	72%	1%	10%	3%	14%	0%	С	0.148	F	0.63	150	G	2019
		Fron			Bus C		40, Lunen	iburg Hwy	′							
735) Pecan St	0.08	80	R			Bu	s US 15				NA			NA		05/26/201
733 . 334. 31	0.00	т.				10.70	0.00 0							107		00/20/201
735) Pecan St	0.02	10 Fron	R			19-78	9 Pecan S	t			NA			NA		05/26/201
735 Pecan St	0.02	To				De	ad End				¬'``			1471		00/20/201
		Fron	1:				SR 59									
739 Wilson St	0.12	150	R								NA			NA		05/15/201
19		Te):			19-76	5 Arvin St	i								
		Fron	1.			19-76	5 Arvin St	i								
757 Osborne St	0.03	360	R								NA			NA		05/26/201
19		Fron).				E, Hill A									
757) Osborne St	0.42	340	G	96%	1%	1%	, Railroad 0%	2%	0%	С	0.109	F	0.525	330	G	2019
757) 3320 31	···-	т.			. , ,				0,0		-	•	0.020	000	O .	_0.0
757) Osborne St	0.14	330 From	R			19-/3	1 Pettus S	ι			NA		-	NA		06/07/201
Osborne St		To				19-722 S	paulding A	Ave								
		Fron	1:				ad End									
758) I St	0.11	20	G	97%	0%	2%	1%	0%	0%	F	0.381	F	0.5	20	G	2019
19/		T/	-				Osborne	St								
758) I St	0.09	130 Fron	G	97%	0%	2%	1%	0%	0%	С	0.126	F	0.529	120	G	2019
197		Te	_				s US 15									

Virginia Department of Transportation Traffic Engineering Division 2019 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Keysville

Length	AADT	QA	4Tire	Bus	3		_	_		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
	From	·									<u> </u>					
0.09	390	R				Dus	0010				NA			NA		05/26/2015
	To	1														
0.05						19-795	Arvin R	d			NΙΔ			ΝΔ		06/07/2018
0.03	320					SF	R 59							INA		00/07/2010
0.45	From		070/	40/			_		00/	_	0.400	-	0.047	400		0040
0.15	130	G	97%	1%					0%		0.130	F	0.647	130	G	2019
0.15	120 From		97%	1%					0%	С	0 127	F	0.563	120	G	2019
0.10	To	Ť	01 70	170					0 70		0.127		0.000	120	ď	2010
	From	:				Bus	US 15									
0.23	70	R									NA			NA		06/12/201
	To															
0.10		<u> </u>				19-716	Farrar S	t			NΙΔ			NΔ		06/07/201
0.10	0 0										INA			INA		00/07/2010
0.10	20 From				19	-796 Sh	adow L	ane			NA			NA		06/07/2018
0.10	To					Dea	d End									00/01/2010
	From	:				SCL K	eysville									
0.38	110	N	97%	2%	. 1	l%	0%	0%	0%	N	0.167	F	0.556	110	Ν	2019
	To From					-757 W,	Osborn	e St			\supset					
0.10	590	F	98%	0%	1		0%	0%	0%	С	0.096	F	0.509	570	F	2019
	F	<u> </u>														
0.05		R				19-774	Priddy S	it			NA			NA		05/19/2019
	To	r				SF	R 59									
					19-82	26 Merr	y Oakes	Lane								
774) Priddy St 0.16 40				R										NA		05/19/2015
	To							it								
0.04										NΙΔ			ΝΔ		06/07/2018	
0.04	To					19-772	Hill Ave							INA		00/01/2010
	From	:														
0.09	50	R									NA			NA		06/07/2018
	To	c			SR	40 Lun	enburg I	lwy								
0.00	From	<u> </u>				19-716	Farrar S	t						NIA		06/07/001/
0.09	70	- К									INA			NA		06/07/2018
0.05	From				19	-796 Sh	adow L	ane			NΙΔ			NΔ		06/07/2018
0.00		_				Dea	d End							INA		00/01/2010
	From															
0.06	80	R									NA			NA		05/26/2015
								t								
0.00						Dea	d End				NIA			NIA		06/07/2018
0.00						19-765	Arvin S	t			INA			INA		00/07/2016
	From	1									l					
0.08	170	R					-				NA			NA		05/19/2015
	To				<u>19</u> -7	87 <u>K</u> eys	sville M	ain St								
0.12	110	R									NA			NA		05/19/2015
		<u> </u>						r								
	From	c				Bus	US 15									
0.10	110	R				Dus					NA			NA		06/12/2018
	0.09 0.05 0.15 0.15 0.23 0.10 0.10 0.38 0.10 0.05 0.16 0.04 0.09 0.09 0.09 0.09 0.09	0.05 320 170 0.15 130 0.15 120 180 0.10 80 0.10 20 10 0.10 590 10 0.10 590 10 0.10 590 10 0.10 70 0.10	0.09 390 R To	0.09 390 R Tor	0.09 390 R Tro Tro Troil	Company Comp	Carry Carr	Company Comp	Company Comp	Dead End Dead End	Carrie	Carry Carr	Carrier	Company Comp	Dead End Dead End	Congress

4/16/2020 9

Virginia Department of Transportation Traffic Engineering Division 2019 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Keysville

Route	Length	AADT	QA	4Tire	Bus	Truck 2Axle 3+Axle 1Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Kevsville								T					
O Laiaura Da	0.15	From				Dead End					NIA		00/10/0010
824 Leisure Dr	0.15	20	R			10.022 Y Y		NA			NA		06/12/2018
		100	1			19-823 June Lane							
		From				19-826 Merry Oaks Lane							
825 Merry Oaks Lane	0.35	40	R					NA			NA		06/07/2018
13)		To	c			SR 59							
		From				WCL Keysville							
826) Merry Oaks Lane	0.10	30	R					NA			NA		06/07/2018
19		To	c			SR 59							

4/16/2020 10